




EZ STIK™ Total Vision is a custom printed adhesive backed white vinyl graphic for exterior retail windows with a printed message on the outside while providing a fully clear “see thru” feature from the inside.

- Designed for window such as storefronts, office buildings and retail applications
- Digital direct full color print
- Completely clear “see thru” appearance from inside
- Short-term use, Up to 24 months durability
- Easy to apply, removable adhesive
- Clean, residue free removal

EZ STIK™ Total Vision (outside mount) provides a unique window viewing experience. Unlike most other perforated window vinyls, this window graphic is the top choice for retail and office treatments because of its completely clear view.

EZ STIK™ Total Vision is a perforated vinyl window graphic that appears opaque from the outside, but allows visibility from the inside. With a specially-designed 60/40 perforation pattern, your graphics achieve a unique one-way appearance that really makes an impact. Printed digital direct in full color, EZ STIK™ Total Vision is the clear choice for short-term window graphics.



Close up showing edge tape finish.

Edge Tape is included with each purchase and is to be applied to the perimeter of the graphic. When used at the time of installation, it extends the life of the graphic and prevents the edges from curling in adverse weather conditions.



Inside View



Outside View


EZ STIK™ Total Vision / Item: EZTV

Use: Outdoor. Apply to exterior retail and office window glass. Life expectancy up to 24 months. Not rated for vehicles (for vehicles use see EZ STIK Window Vision)

Media: 7mil perforated 60/40 window vinyl

Adhesive: acrylic, medium-tack, removable

Finishing Cut Options – While many EZ STIK™ graphics can be custom shape cut, EZ STIK™ Window Vision is recommended for a square cut only.



Standard Square Cut

Rectangle or square shape with straight sides and square corners.



Close up showing the hole pattern.
Print Side white(front) / Adhesive side black (back)

General Application Instructions


For specialty graphics to properly adhere, the application surface must be clean: free of oils, grease, dust, and debris.

Apply all specialty graphics in temperatures that are neither too hot nor too cold. The optimum temperature for installing is between 65° and 72°F. Graphics can be installed as low as 50° and up to 90°F. Larger outdoor graphics are easier to apply in the protection of shade.

Windows/Glass: Install on a clean and dry surface. Clean glass surface with water or a common glass cleaner. Best practices: A razor-blade scraper with glass cleaner (or water) can be used to remove little bits of crud. Using a paper towel or lint-free rag, wipe glass surface with isopropyl alcohol or denatured alcohol.

Other Surfaces: For all other applications, make sure surface is clean and dry. Choose a location to test graphic adhesion. Because surface conditions and properties can vary widely, it is ultimately the responsibility of the end user to test the bond and effective removal of the adhesive graphic from the chosen surface.

Method: Use overlapping strokes as you apply the graphic to the surface. If you don't have an installation squeegee, a stiff plastic (like a credit card) can be helpful to smooth the graphic out during application.



1) Surface Prep.
Wipe glass clean.



2) Peel.
Begin to remove backing.



3) Stick.
Use overlapping strokes to apply the graphic.



4) Apply Pressure.
With a wiping motion, firmly press entire surface to activate adhesive.

For video demonstrations of specialty graphics applications, including tips and techniques, visit: amatterofgraphics.com